



PULSEAUDIO™

MICROPHONE

# PREAMPLIFIER



## PART NUMBER PA-MICPRE

Small, simple, and easy to use microphone pre-amplification solution

[vanco1.com](http://vanco1.com) | 800.626.6445

# DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference.

THIS PRODUCT IS 100% INSPECTED AND TESTED IN THE UNITED STATES TO VERIFY PERFORMANCE PARAMETERS.

---

## WARNING

1. Do not install or place this unit in a built-in cabinet, or other confined space without adequate ventilation.
2. To prevent risk of electrical shock or fire hazard, due to overheating do not obstruct unit's ventilation openings.
3. Do not install near any source of heat, including other units that may produce heat.
4. Do not place unit near flames.
5. Only clean unit with a dry cloth.
6. Unplug unit during lightning storms or when not used for an extended period of time.
7. Protect the power cord from being walked on or pinched, particularly at the plugs.
8. Use unit only with accessories specified by the manufacturer.
9. Refer all servicing to qualified personnel.

## o FEATURES

The PulseAudio PA-MICPRE is a microphone preamplifier that provides a small, simple, and easy to use microphone pre-amplification solution for a variety of applications. Featuring both balanced XLR and unbalanced 1/4" inputs and outputs, along with a single gain control with a clipping indicator. The 1/4" output is uniquely designed for use as a mono unbalanced output, or a stereo headphone output. Phantom power option is provided for use with a condenser microphones. For any applications requiring a microphone to be added, the PA-MICPRE is a great solution that is simple and easy to use!

## Microphone Preamplifier o Part # PA-MICPRE

- XLR and 1/4" inputs and outputs
- 1/4" output for mono or stereo applications
- Input impedance 10K ohm (balanced/unbalanced)
- Max input level +4dBv balanced, +10dBv unbalanced
- Manual gain control
- Clipping indicator
- 36V phantom power
- Dimensions: 4.4" x 2.8" x 1.5"

## o PACKAGE CONTENTS

- PA-MICPRE Microphone Preamplifier
- 12V Power Supply
- Product Manual

## ◦ PANEL DESCRIPTIONS

### FRONT PANEL



### BACK PANEL



1. Power LED
2. 36V Phantom Power (enabled with button depressed)
3. Clip indicator
4. Gain dial
5. 1/4" Unbalanced Input
6. XLR Female Balanced Input
7. XLR Male Balanced Output
8. 1/4" Unbalanced Output
9. 12V Power Input

## ○ CONNECT AND OPERATE



1. With the PA-MICPRE powered off, connect a microphone with either the XLR or 1/4" Input
2. Note: If using a condenser microphone, make sure the Phantom Power button is depressed
3. Connect the output of the PA-MICPRE to the amplifier using the XLR or 1/4" outputs
4. Apply power to the PA-MICPRE and amplifier
5. Adjust the gain on the PA-MICPRE and/or volume and settings on the amplifier for the desired audio levels

## ○ SPECIFICATIONS

Input Impedance.....	10K ohm balanced/unbalanced
Max Level Input.....	+4 dBV XLR, +10 dBV 1/4"
Max Gain.....	50dB XLR, 44 dB 1/4"
Phase Shift.....	<10 deg. 20Hz-20kHz
EIN.....	129 dB max
THD.....	<.01%
IMD (SMPTE).....	<.01%
Power.....	12V DC Adapter
Dimension.....	4.4" Wx 2.8" H x 1.5"D
Weight.....	0.8 lbs

## ○ SAFETY AND NOTICE

The PA-MICPRE has been tested for conformance to safety regulations and requirements, and has been certified for international use. However, like all electronic equipment, the PA-MICPRE should be used with care. Please read and follow the safety instructions to protect yourself from possible injury and to minimize the risk of damage to the unit.

- Follow all instructions and warnings marked on this unit.
- Do not attempt to service this unit yourself, except where explained in this manual.
- Provide proper ventilation and air circulation and do not use near water.
- Keep objects that might damage the device and assure that the placement of this unit is on a stable surface.
- Use only the power adapter and power cords and connection cables designed for this unit.
- Do not use liquid or aerosol cleaners to clean this unit.
- Always unplug the power to the device before cleaning

## ◦ TECHNICAL SUPPORT

In case of problems, please contact Vanco Technical Support by dialing 1-800-626-6445. You can also email technical support issues to [techsupport@vanco1.com](mailto:techsupport@vanco1.com). When calling, please have the Model Number, Serial Number (affixed to the bottom of the unit) and Invoice available for reference during the call. Please read this Instruction Manual prior to calling or installing this unit, since it will familiarize you with the capabilities of this product and its proper installation. All active electronic products are 100% inspected and tested to insure highest product quality and trouble-free installation and operation. The testing process utilizes the types of high-definition sources and displays typically installed for entertainment and home theatre applications. For additional information please visit [www.vanco1.com](http://www.vanco1.com).

## ◦ LIABILITY STATEMENT

Every effort has been made to ensure that this product is free of defects. The manufacturer of this product cannot be held liable for the use of this hardware or any direct or indirect consequential damages arising from its use. It is the responsibility of the user and installer of the hardware to check that it is suitable for their requirements and that it is installed correctly. All rights are reserved. No parts of this manual may be reproduced or transmitted by any form or means electronic or mechanical, including photocopying, recording or by any information storage or retrieval system without the written consent of the publisher. Manufacturer reserves the right to revise any of its hardware and software following its policy to modify and/or improve its products where necessary or desirable. This statement does not affect the legal rights of the user in any way.

## ◦ LIMITED WARRANTY

With the exceptions noted in the next paragraph, Vanco warrants to the original purchaser that the equipment it manufactures or sells will be free from defects in materials and workmanship for a period of two years from the date of purchase. Should this product, in Vanco's opinion, prove defective within this warranty period, Vanco, at its option, will repair or replace this product without charge. Any defective parts replaced become the property of Vanco. This warranty does not apply to those products which have been damaged due to accident, unauthorized alterations, improper repair, modifications, inadequate maintenance and care, or use in any manner for which the product was not originally intended. Items integrated into Vanco products that are made by other manufacturers, notably computer hard drives and liquid crystal display panels, are limited to the term of the warranty offered by the respective manufacturers. Such specific warranties are available upon request to Vanco. A surge protector, power conditioner unit, or an uninterruptible power supply must be installed in the electrical circuit to protect against power surges. If repairs are needed during the warranty period the purchaser will be required to provide a sales receipt/sales invoice or other acceptable proof of purchase to the seller of this equipment. The seller will then contact Vanco regarding warranty repair or replacement.

## **Vanco® International**

506 Kingsland Drive Batavia, Illinois 60510

call: 800.626.6445 | fax: 630.879.9189

visit: [www.vanco1.com](http://www.vanco1.com)

A brand from



Learn more at [vanco1.com](http://vanco1.com)